

170N1440

High-speed fuses uR without striker NFC Fuselink UR 40A 690 VAC



SOCOMECE High-speed fuses (UR) protect power semiconductors and DC circuits.

Strong points

- High-performance
- Increased reliability
- Improved safety
- Fuse blown indicator

Compliance with standards

- IEC 60269-1
- NF EN 60269-1
- IEC 60269-4
- NF EN 60269-4
- DIN EN 60269-4

Access to resources (ex: manuals)



<https://www.socomec.co.uk/en-gb/reference/170N1440>

Technical Characteristics

Fuse melting indicator	without striker
Fuse size	14x51
Rated voltage	690 VAC
Rated current [A]	40
Type	uR/aR

Classification

UNSPSC	39121628
ETIM Class	EC002704
IGCC	4982

Commerce

Effective date	2006-07-07
Offer Life Cycle Code	40
Country of origin	IN

ETIM - Electrical characteristics

Rated current [A]	40
Rated voltage DC [V]	690
Voltage type	AC/DC
Utilization category according to IEC 60269	aR
Rated operating frequency [Hz]	50..60
Release characteristic	Fast (F)
Breaking capacity at nominal voltage, AC [kA]	200

ETIM - Mechanical characteristics

Size	14x51 mm
------	----------

ETIM - Technical features

Model	Ceramic fuse
-------	--------------

Logistics

GTIN/EAN	3596031838004
Customs number	8536105090
Price unit	PC
Weight of the packing unit [kg]	0.201
Length of the packing unit [m]	0.051
Width of the packing unit [m]	0.014
Depth of the packing unit [m]	0.014

Norms

Conformity to standards	IEC UL
-------------------------	------------