

192A4428

## Analog ammeter D96A90-A 0-2000A CT 5A



### Strong points

- Extensive range
- Made in Europe
- Many accessories

### General characteristics

- Deflection: 90°.
- DIN and ROTEX indicators.
- Insulation voltage 660 V.
- Dielectric quality 2 kV - 50 Hz - 1 mn.
- Consumption: 1.1 VA.
- Operating frequency: 45/65 Hz.
- Motor rating 5 In: use on motor circuits up to 8 In.
- Connection: screw mounted, with FASTON lugs for any rating ? 15 A

Ferromagnetic ammeters measure the alternating current of any electrical circuit. They are embedded in the front panel of cabinets, enclosures or other equipment.

### Classification

UNSPSC	41113637
ETIM Class	EC002292
IGCC	6303

### Commerce

Effective date	1998-02-09
Country of origin	ES

### ETIM - Electrical characteristics

Nominal end value of the scale [A]	2000
Measuring range [A]	0..2000
Accuracy class	1.5
Power loss [W]	1.1
Voltage type	AC
Overcurrent scale	No
Calibrated	Yes
Stay-set indicator	No

### ETIM - Mechanical characteristics

Transformer connection	Yes
Modular version	No
Width [mm]	96
Height [mm]	96

### ETIM - Technical features

Model	Built-in
Max. needle deflection [°]	90

### Logistics

GTIN/EAN	3596031073559
Customs number	9030337000
Price unit	PC
Weight of the packing unit	0.26
Length of the packing unit	0.08
Width of the packing unit	0.12
Depth of the packing unit	0.12

### Technical Characteristics

Deflection	90° In
Rated current	2000
Type	AC Analog Ammeter DIN96 90° /5A