

192B3315

Analog ammeter D72A90-A 0-20A CT 5A



Strong points

- Extensive range
- Made in Europe
- Many accessories

General characteristics

- Deflection: 90°.
- DIN and ROTEX indicators.
- Insulation voltage 660 V.
- Dielectric quality 2 kV - 50 Hz - 1 mn.
- Consumption: 1.1 VA.
- Operating frequency: 45/65 Hz.
- Motor rating 5 In: use on motor circuits up to 8 In.
- Connection: screw mounted, with FASTON lugs for any rating ? 15 A

Ferromagnetic ammeters measure the alternating current of any electrical circuit. They are embedded in the front panel of cabinets, enclosures or other equipment.

Classification

| | |
|------------|----------|
| UNSPSC | 41113637 |
| ETIM Class | EC002292 |
| IGCC | 6303 |

Commerce

| | |
|-------------------|------------|
| Effective date | 1998-02-09 |
| Country of origin | ES |

ETIM - Electrical characteristics

| | |
|------------------------------------|-------|
| Nominal end value of the scale [A] | 20 |
| Measuring range [A] | 0..20 |
| Accuracy class | 1.5 |
| Power loss [W] | 1.1 |
| Voltage type | AC |
| Overcurrent scale | No |
| Calibrated | Yes |
| Stay-set indicator | No |

ETIM - Mechanical characteristics

| | |
|------------------------|-----|
| Transformer connection | Yes |
| Modular version | No |
| Width [mm] | 72 |
| Height [mm] | 72 |

ETIM - Technical features

| | |
|----------------------------|----------|
| Model | Built-in |
| Max. needle deflection [°] | 90 |

Logistics

| | |
|----------------------------|---------------|
| GTIN/EAN | 3596031075423 |
| Customs number | 9030337000 |
| Price unit | PC |
| Weight of the packing unit | 0.199 |
| Length of the packing unit | 0.08 |
| Width of the packing unit | 0.1 |
| Depth of the packing unit | 0.1 |

Technical Characteristics

| | |
|---------------|-------------------------------------|
| Deflection | 90° 5 x In |
| Rated current | 20 |
| Type | AC Analog Ammeter DIN72 90° /5A 5IN |