

192G1007

Analog voltmeter D48A90-V DIN 48x48 0-500V



Strong points

- Extensive range
- Made in Europe
- Many accessories

General characteristics

- Deflection: 90°.
- Insulating voltage: 660 V.
- Dielectric quality 2 kV - 50 Hz - 1 mn.
- Consumption: 3 VA.
- Operating frequency: 45/65 Hz.
- Connection: screw or FASTON lugs.

Compliance with standards

- IEC 60051-1
- IEC 60414
- NF EN 60051-1
- DIN 43780
- NF C 42-010
- VDE 0410
- BS 5448
- BS 89

Access to resources (ex: manuals)

<https://www.socomec.co.uk/en-gb/reference/192G1007>

Ferromagnetic voltmeters measure the AC voltage of any electrical circuit. They are embedded in the front panel of cabinets, enclosures or other equipment.

Classification	
UNSPSC	41113637
ETIM Class	EC002306
IGCC	6303
Commerce	
Effective date	1998-02-09
Country of origin	ES
ETIM - Electrical characteristics	
Measuring range [V]	500..500
Accuracy class	1.5
Power loss [W]	3
Calibrated	Yes
Voltage type	AC
ETIM - Mechanical characteristics	
Transformer connection	No
Modular version	Yes
Width [mm]	48
Height [mm]	48
ETIM - Technical features	
Model	DIN rail
Max. needle deflection [°]	90
Scales lighting	No
Logistics	
GTIN/EAN	3596031084104
Customs number	9030337000
Price unit	PC
Weight of the packing unit	0.111
Length of the packing unit	0.065
Width of the packing unit	0.05
Depth of the packing unit	0.09
Technical Characteristics	
Rated voltage	0..500 VAC
Scale nominal value	90°
Type	D48x48