

192Y0602

## CTA-VA4 5A/4-20mA ALIM 230V



### Strong points

- Compact
- Different levels of output
- Different levels of power supply

### General characteristics

- Input:
  - Direct connection 0 to 10 A
  - CT primary, 50 to 400 A (self-powered)
  - CT primary, 15 to 500 A (auxiliary power supply).
- Output:
  - 0-20 mA, 0 -10 V (model CTA-VA)
  - 4-20 mA and 0-10 V (model CTA-VA4).
- Self-powered or auxiliary power supply 24 VDC or 230 VAC.
- Dimensions: 135 x 80 x 50 mm.

### Compliance with standards

- NF C 15-100 articles 473.1.4-556.3
- GAM EG 13.C (military standard)

### Access to resources (ex: manuals)

<https://www.socomec.co.uk/en-gb/reference/192Y0602>

Compact measurement converter with bypass transformer unit with cables (Ø 27 mm) or busbars (40 x 10 mm).

<b>Classification</b>	
UNSPSC	41112112
ETIM Class	EC002478
IGCC	3240
<b>Commerce</b>	
Effective date	1998-04-20
Country of origin	DE
<b>ETIM - Electrical characteristics</b>	
Type of analogy output	4 - 20 mA
Number of phases	1
<b>ETIM - Mechanical characteristics</b>	
Modular version	No
<b>Logistics</b>	
GTIN/EAN	3596031094882
Customs number	8504408390
Price unit	PC
Weight of the packing unit	0.38
Length of the packing unit	0.08
Width of the packing unit	0.1
Depth of the packing unit	0.14
<b>Norms</b>	
Conformity to standards	IEC
<b>Technical Characteristics</b>	
Control voltage	230 VAC
Input	5A
Output	4-20mA / 0-10VDC
Type	Current transducer