

192Y0605

CTA-VA4 20A/4-20mA ALIM 230V



Strong points

- Compact
- Different levels of output
- Different levels of power supply

General characteristics

- Input:
 - Direct connection 0 to 10 A
 - CT primary, 50 to 400 A (self-powered)
 - CT primary, 15 to 500 A (auxiliary power supply).
- Output:
 - 0-20 mA, 0 -10 V (model CTA-VA)
 - 4-20 mA and 0-10 V (model CTA-VA4).
- Self-powered or auxiliary power supply 24 VDC or 230 VAC.
- Dimensions: 135 x 80 x 50 mm.

Compliance with standards

- NF C 15-100 articles 473.1.4-556.3
- GAM EG 13.C (military standard)

Access to resources (ex: manuals)

<https://www.socomec.co.uk/en-gb/reference/192Y0605>

Compact measurement converter with bypass transformer unit with cables (Ø 27 mm) or busbars (40 x 10 mm).

Classification	
UNSPSC	41112112
ETIM Class	EC002478
IGCC	3240
Commerce	
Effective date	1998-04-20
Country of origin	DE
ETIM - Electrical characteristics	
Type of analogy output	4 - 20 mA
Number of phases	1
ETIM - Mechanical characteristics	
Modular version	No
Logistics	
GTIN/EAN	3596031094912
Customs number	8504408390
Price unit	PC
Weight of the packing unit	0.392
Length of the packing unit	0.08
Width of the packing unit	0.088
Depth of the packing unit	0.146
Norms	
Conformity to standards	IEC
Technical Characteristics	
Control voltage	230 VAC
Input	20A
Output	4-20mA / 0-10VDC
Type	Current transducer