

36556041

Switch-discon-fuse visi break FUSOMAT ST coil-Ext&dir R OP-400A-4P-DIN-Fuse S2



Strong points

- Tripping upon overload
- High breaking capacity
- Improved safety

Compliance with standards

- IEC 60947-3

Access to resources (ex: manuals)

<https://www.socomec.co.uk/en-gb/reference/36556041>

They can be tripped remotely.

They break or switch off on load and provide safety isolation and protection against overcurrent for any low voltage electrical circuit.

They can automatically disconnect a circuit in combination with:

- fuse blown indication.
- thermal relay.
- other protective devices.

Can be combined with UR fuses for the protection of power semi-conductors.

Classification

UNSPSC	39122233
ETIM Class	EC001040
IGCC	5291

Commerce

Effective date	1992-01-22
Country of origin	FR

ETIM - Electrical characteristics

Max. rated operation voltage Ue AC [V]	690
Rated permanent current Iu [A]	400
Number of poles	4

ETIM - Mechanical characteristics

Cable entry	Top/bottom
Equipped with connectors	No
Suitable for floor mounting	Yes
Suitable for front mounting	Yes
Suitable for busbar mounting	No
Degree of protection (IP), front side	IP20

ETIM - Technical features

Version as main switch	Yes
Version as safety switch	Yes
Suitable for fuses	NH2
With error protection	No
Type of electrical connection of main circuit	Bolt connection
Type of control element	Long turning handle
Position control element	Left
Motor drive optional	No
Motor drive integrated	No
Version as emergency stop installation	Yes

Logistics

GTIN/EAN	3596031185948
Customs number	8536309090
Price unit	PC
Weight of the packing unit	10.165

Norms

Conformity to standards	IEC
-------------------------	-----

Technical Characteristics

Fuse size	NH2
-----------	-----

Number of poles	4
Rated current	400
Type	I-0