

**41503012**

## Manually operated transfer switch body SIRCOVER UL1008 3P 100A

### Strong points

- Stable positions
- Compact design
- On-load switching
- Reliability

### General characteristics

- Range from 100A to 1200A.
- Available in 2P, 3P or 4P.
- Direct handle or external handle.

### Compliance with standards

- UL 1008, Guide WPHY, file 317092
- UL 98, Guide WHTY, file 201138

### Access to resources (ex: manuals)

<https://www.socomec.co.uk/en-gb/reference/41503012>

SIRCOVER UL 98/1008 are heavy duty manual transfer switches. They ensure switching transfer of sources or transfer of two low voltage circuits on load as well as their safe disconnection.

These switches are extremely durable and are tested and approved for use in the most demanding applications, such as resistive load or total system applications

### Classification

UNSPSC	39122205
ETIM Class	EC000216
IGCC	5177

### Commerce

Effective date	2013-07-09
Country of origin	FR
Length of the product unit	0.135
Width of the product unit	0.244
Depth of the product unit	0.176
Weight	5.92

### ETIM - Electrical characteristics

Max. rated operation voltage Ue AC [V]	600
Rated operating voltage [V]	240..600
Rated permanent current Iu [A]	100
Number of poles	3

### ETIM - Mechanical characteristics

Suitable for floor mounting	No
Suitable for front mounting 4-hole	No
Suitable for front mounting centre	No
Suitable for distribution board installation	No
Suitable for intermediate mounting	Yes
Colour control element	Black
Degree of protection (IP), front side	IP20

### ETIM - Technical features

Version as main switch	Yes
Version as maintenance-/service switch	Yes
Version as safety switch	Yes
Version as emergency stop installation	No
Version as reversing switch	Yes
Number of switches	2
Motor drive optional	No
Motor drive integrated	No
Voltage release optional	No
Device construction	Built-in device fixed built-in technique
Type of control element	Door coupling rotary drive
Interlockable	Yes
Type of electrical connection of main circuit	Bolt connection

### Logistics

GTIN/EAN	3596032759452
Customs number	8536508090
Price unit	PC

Weight of the packing unit	5.92
Length of the packing unit	0.38
Width of the packing unit	0.38
Depth of the packing unit	0.255
<b>Norms</b>	
Conformity to standards	UL
<b>Technical Characteristics</b>	
Number of poles	3
Rated current	100