

41503022

Manually operated transfer switch body SIRCOVER UL1008 3P 200A

Strong points

- Stable positions
- Compact design
- On-load switching
- Reliability

General characteristics

- Range from 100A to 1200A.
- Available in 2P, 3P or 4P.
- Direct handle or external handle.

Compliance with standards

- UL 1008, Guide WPHY, file 317092
- UL 98, Guide WHTY, file 201138

Access to resources (ex: manuals)

<https://www.socomec.co.uk/en-gb/reference/41503022>

SIRCOVER UL 98/1008 are heavy duty manual transfer switches. They ensure switching transfer of sources or transfer of two low voltage circuits on load as well as their safe disconnection.

These switches are extremely durable and are tested and approved for use in the most demanding applications, such as resistive load or total system applications

Classification

| | |
|------------|----------|
| UNSPSC | 39122205 |
| ETIM Class | EC000216 |
| IGCC | 5177 |

Commerce

| | |
|----------------------------|------------|
| Effective date | 2013-07-09 |
| Country of origin | FR |
| Length of the product unit | 0.135 |
| Width of the product unit | 0.244 |
| Depth of the product unit | 0.176 |
| Weight | 5.92 |

ETIM - Electrical characteristics

| | |
|--|----------|
| Max. rated operation voltage Ue AC [V] | 600 |
| Rated operating voltage [V] | 240..600 |
| Rated permanent current Iu [A] | 200 |
| Number of poles | 3 |

ETIM - Mechanical characteristics

| | |
|--|-------|
| Suitable for floor mounting | No |
| Suitable for front mounting 4-hole | No |
| Suitable for front mounting centre | No |
| Suitable for distribution board installation | No |
| Suitable for intermediate mounting | Yes |
| Colour control element | Black |
| Degree of protection (IP), front side | IP20 |

ETIM - Technical features

| | |
|---|--|
| Version as main switch | Yes |
| Version as maintenance-/service switch | Yes |
| Version as safety switch | Yes |
| Version as emergency stop installation | No |
| Version as reversing switch | Yes |
| Number of switches | 2 |
| Motor drive optional | No |
| Motor drive integrated | No |
| Voltage release optional | No |
| Device construction | Built-in device fixed built-in technique |
| Type of control element | Door coupling rotary drive |
| Interlockable | Yes |
| Type of electrical connection of main circuit | Bolt connection |

Logistics

| | |
|----------------|---------------|
| GTIN/EAN | 3596032759506 |
| Customs number | 8536508090 |
| Price unit | PC |

| | |
|----------------------------------|------|
| Weight of the packing unit | 5.92 |
| Length of the packing unit | 0.32 |
| Width of the packing unit | 0.42 |
| Depth of the packing unit | 0.3 |
| Norms | |
| Conformity to standards | UL |
| Technical Characteristics | |
| Number of poles | 3 |
| Rated current | 200 |