

41503041

Manually operated transfer switch body SIRCOVER UL1008 3P 400A

Strong points

- Stable positions
- Compact design
- On-load switching
- Reliability

General characteristics

- Range from 100A to 1200A.
- Available in 2P, 3P or 4P.
- Direct handle or external handle.

Compliance with standards

- UL 1008, Guide WPYV, file 317092
- UL 98, Guide WHTY, file 201138

Access to resources (ex: manuals)

<https://www.socomec.co.uk/en-gb/reference/41503041>

SIRCOVER UL 98/1008 are heavy duty manual transfer switches. They ensure switching transfer of sources or transfer of two low voltage circuits on load as well as their safe disconnection.

These switches are extremely durable and are tested and approved for use in the most demanding applications, such as resistive load or total system applications

Classification

UNSPSC	39122205
ETIM Class	EC000216
IGCC	5177

Commerce

Effective date	2009-11-10
Country of origin	TN
Length of the product unit	0.195
Width of the product unit	0.301
Depth of the product unit	0.1655
Weight	12.05

ETIM - Electrical characteristics

Max. rated operation voltage Ue AC [V]	600
Rated operating voltage [V]	240..600
Rated permanent current Iu [A]	400
Number of poles	3

ETIM - Mechanical characteristics

Suitable for floor mounting	No
Suitable for front mounting 4-hole	No
Suitable for front mounting centre	No
Suitable for distribution board installation	No
Suitable for intermediate mounting	Yes
Colour control element	Black
Degree of protection (IP), front side	IP20

ETIM - Technical features

Version as main switch	Yes
Version as maintenance-/service switch	Yes
Version as safety switch	Yes
Version as emergency stop installation	No
Version as reversing switch	Yes
Number of switches	2
Motor drive optional	No
Motor drive integrated	No
Voltage release optional	No
Device construction	Built-in device fixed built-in technique
Type of control element	Door coupling rotary drive
Interlockable	Yes
Type of electrical connection of main circuit	Bolt connection

Logistics

GTIN/EAN	3596031982011
Customs number	8536508090
Price unit	PC

Weight of the packing unit	12.05
Length of the packing unit	0.321
Width of the packing unit	0.407
Depth of the packing unit	0.481
Norms	
Conformity to standards	UL
Technical Characteristics	
Number of poles	3
Rated current	400