

48250207

Energy monitoring and event analysis DIRIS A-60 110-400VAC/120-350VDC



Strong points

- Easy to use
- Detects wiring errors
- Compliant with IEC 61557-12
- Software tools
- EN 50160 compliant

Compliance with standards

- IEC 61557-12
- IEC 62053-22 Class 0.5S
- IEC 62053-23 Class 2
- EN 50160

Access to resources (ex: manuals)



<https://www.socomec.co.uk/en-gb/reference/48250207>

DIRIS A60 is a power monitoring device (PMD) that incorporates all the functions of the DIRIS A-30.

In addition, it offers logging and viewing of events that are harmful to the installation. All this information can be used and analysed remotely via the free Analysis software, which can be downloaded from the website www.socomec.com

Technical Characteristics

Application	Analysis
Communication ports	Optional RS485 or Ethernet
Communication protocols	Optional Modbus RTU, TCP or Profibus
Model	A60

Classification

UNSPSC	83101808
ETIM Class	EC002301
IGCC	6042

Commerce

Description	DIRIS A-60 110-400VAC / 120-350VDC with Modbus or Profibus communication protocols / RS485 or Ethernet communication ports panel mounted multifunction meter
Effective date	2009-04-28
Offer Life Cycle Code	40
Country of origin	TN

ETIM - Technical features

Ampere meter	Yes
Blind power meter	Yes
With rotational speed meter	No
Frequency meter	Yes
Pulse counter	No
Voltmeter	Yes
Effective power measurement device	Yes

Logistics

GTIN/EAN	3596031961443
Customs number	9030310090
Price unit	PC
Weight of the packing unit [kg]	0.69
Length of the packing unit [m]	0.24
Width of the packing unit [m]	0.16
Depth of the packing unit [m]	0.12

Norms

Conformity to standards	IEC
-------------------------	-----