

48250502

Multifunction meter DIRIS A-40 communication Sub D9 PROFIBUS DP I/O:3/2



Strong points

- Assisted configuration
- Facilitated integration
- Connected to the Cloud
- Compliant with IEC 61557-12

General characteristics

- Assisted configuration.
- Connected to the Cloud.
- Compliant with IEC 61557-12.
- Smart sensors.

Compliance with standards

- IEC 61557-12
- EN 50160
- UL61010 E257746

Access to resources (ex: manuals)

<https://www.socomec.co.uk/en-gb/reference/48250502>

The DIRIS A-40 is a door-mounted power monitoring device (PMD) in 96 x 96 format. It is intended for the measurement, monitoring and management of electrical energy.

The DIRIS A-40 provides numerous functions for measuring voltage, current, power, energy and quality.

It allows the analysis of a single-phase or three-phase load.

Classification

UNSPSC	83101808
ETIM Class	EC002301
IGCC	6042

Commerce

Effective date	2017-03-23
Country of origin	FR

ETIM - Electrical characteristics

Accuracy class active energy according to IEC 62053-22	0.2S
Sampling frequency [Hz]	10
Number of voltage measurement inputs	5
Number of current measurement inputs	3
Voltage type (supply voltage)	AC/DC
Supply voltage DC [V]	120..120
Measuring range for frequency [Hz]	45..65
Number of analogue outputs	2
Number of digital inputs	3
Number of Ethernet-connections	1
Supporting protocol for PROFIBUS	No
Supporting protocol for Modbus	Yes
Supporting protocol for other bus systems	No
Web server with HTTPS transfer protocol	No

ETIM - Mechanical characteristics

Width [mm]	98
Height [mm]	98
Depth [mm]	85

ETIM - Technical features

Ampere meter	Yes
Blind power meter	Yes
With rotational speed meter	No
Frequency meter	Yes
Pulse counter	Yes
Voltmeter	Yes
Effective power measurement device	Yes
Display	LCD
Remote display	No

Logistics

GTIN/EAN	3596033009143
Customs number	9030310090
Price unit	PC

Weight of the packing unit	0.425
Length of the packing unit	0.1
Width of the packing unit	0.12
Depth of the packing unit	0.11
Norms	
Conformity to standards	IEC UL
Technical Characteristics	
Application	Analysis
Communication ports	Profibus DP
Communication protocols	Profibus
Model	A40
Type	3 inputs/2 outputs