

48290185

Branch-circuit monitoring RJ45 cable Digiware bus - 50m 100 connectors



General characteristics

- Available in different lengths.
- 600V insulated, can be in contact with busbars.
- Plug & Play.

Compliance with standards

- IEC 61557-12
- UL 61010 Guide FTRZ/PICQ File E257746

Access to resources (ex: manuals)



<https://www.socomec.co.uk/en-gb/reference/48290185>

The RJ45 connections allow you to connect modules very quickly and to automatically configure connected current sensors:

- communication address,
 - load type,
 - sensor type and ratio,
 - automatic rating and verification of current travel direction.
- Wiring errors are also prevented and installation is simplified.

Technical Characteristics

Height [mm]	50000
Color	Yellow
Connector	RJ45
Length	50 m
Type	Digiware bus

Classification

UNSPSC	83101808
ETIM Class	EC001262
IGCC	6042

Commerce

Effective date	2014-04-29
Offer Life Cycle Code	40
Country of origin	TH

ETIM - Mechanical characteristics

Length [m]	50
Colour outer sheath	Yellow
Anti-kink sleeve	None
Colour anti-kink sleeve	Other
Cable construction	2x4
AWG-size	24
Cable type	U/UTP

ETIM - Technical features

Category	5
Type of connector connection 1	RJ45 8(8)
Type of connector connection 2	RJ45 8(8)
Locking lever	No
Fire retardant version	No
Oil resistant according to EN IEC 60811-404	Yes
Pin assignment	1:1
NVP value [%]	70

Logistics

GTIN/EAN	3596032804558
Customs number	8544429090
Price unit	PC
Weight of the packing unit [kg]	1.94
Length of the packing unit [m]	0.23
Width of the packing unit [m]	0.23
Depth of the packing unit [m]	0.055

Norms

Conformity to standards

IEC
UL