

**54111017**

## DISTRIBUTION BLOCK UNIPOLAR 175 A IEC AND 175 A UR



### Strong points

- Extensive range
- IEC and UL range
- Easy integration

### General characteristics

IEC/UL distributors:

- Material: tin-plated aluminium.
- For conductors: aluminium or copper.
- IP20 connection.
- L1, L2, L3, N marking adjusted by Allen key.
- DIN rail-mounted.
- DIN rail attachment clip.
- Board-mounted.
- Assembly clip for multiple distribution blocks.

IEC/UR distributors:

- Material: treated aluminium for types 1 to 5, uncoated brass for types 6 to 8.
- For conductors: Aluminium or copper for types 1 to 5, copper for types 6 to 8.
- IP20 connection.
- DIN rail-mounted.
- Board-mounted.

### Compliance with standards

- IEC 61439-1
- IEC 60947-7-1
- UL 1953
- UL 1059

### Access to resources (ex: manuals)

<https://www.socomec.co.uk/en-gb/reference/54111017>

Distributors provide an easy connection to conductors. They are mounted downstream of a load break switch, changeover switch, a fuse switch or any protection device on the market.

<b>Classification</b>	
UNSPSC	39121421
ETIM Class	EC000276
IGCC	4586
<b>Commerce</b>	
Effective date	2018-03-06
Country of origin	FR
Length of the product unit	0.045
Width of the product unit	0.071
Depth of the product unit	0.043
Weight	0.115
<b>ETIM - Mechanical characteristics</b>	
Number of poles	1
With seal head	No
<b>Logistics</b>	
GTIN/EAN	3596033047596
Customs number	8536901000
Price unit	PC
Weight of the packing unit	0.121
Length of the packing unit	0.05
Width of the packing unit	0.05
Depth of the packing unit	0.1
<b>Norms</b>	
Conformity to standards	IEC UL
<b>Technical Characteristics</b>	
Number of conductors	11
Number of poles	1
Rated current	175