

**57010016**

## RM cylind. fuse holder for neutral without aux. cont.-32A-1P-NFC-Fuse 10x38



### Strong points

- Improved safety
- High breaking capacity
- Format and specific accessories

### General characteristics

- Improved safety.
- High breaking capacity.
- Features and options.

### Compliance with standards

- IEC 60269-2,-1
- IEC 60269-1
- IEC 60269-2
- UL E307648

### Access to resources (ex: manuals)

<https://www.socomec.co.uk/en-gb/reference/57010016>

RMs are modular fuse disconnect switches for cylindrical fuses. They ensure safe disconnection and protection against surges and short-circuits in any low voltage electrical circuit.

<b>Classification</b>	
UNSPSC	39121624
ETIM Class	EC002705
IGCC	4974
<b>Commerce</b>	
Effective date	2012-06-25
Country of origin	ES
Length of the product unit	0.078
Width of the product unit	0.07
Depth of the product unit	0.058
Weight	0.061
<b>ETIM - Electrical characteristics</b>	
Nominal voltage [V]	690
Number of poles	1
Concurrently switching neutral conductor	Yes
<b>ETIM - Mechanical characteristics</b>	
Built-in depth [mm]	40
Degree of protection (IP)	IP2X
Mounting method	DIN rail
For fuse size	10x38 mm
Width in number of modular spacings	1
<b>ETIM - Technical features</b>	
Lockable	Yes
With optical defect indication	No
<b>Logistics</b>	
GTIN/EAN	3596032686895
Customs number	8536105090
Price unit	PC
Weight of the packing unit	0.06
Length of the packing unit	0.09
Width of the packing unit	0.065
Depth of the packing unit	0.02
<b>Norms</b>	
Conformity to standards	IEC UL
<b>Technical Characteristics</b>	
Fuse melting indicator	No
Fuse size	10x38
Number of poles	1
Rated current	32
Size	RM32