

57025011

RMS cylind. fuse holder with front operated sign. aux. cont 14x51 1P 50 A



Strong points

- Improved safety
- High breaking capacity
- Format and specific accessories

General characteristics

- Improved safety.
- High breaking capacity.
- Features and options.

Compliance with standards

- IEC 60269-2,-1
- IEC 60269-1
- IEC 60269-2
- UL E307648

Access to resources (ex: manuals)

<https://www.socomec.co.uk/en-gb/reference/57025011>

RMS are modular fuse disconnect switches for cylindrical fuses. They provide safety disconnection and protection against overloads and short-circuits in any low voltage electrical circuit.

RMS: Fuse disconnect switches with pre-breaking auxiliary contact that signals that the fuse is present / blown.

| | |
|--|---------------|
| Classification | |
| UNSPSC | 39121624 |
| ETIM Class | EC002705 |
| IGCC | 4974 |
| Commerce | |
| Effective date | 2005-11-04 |
| Country of origin | ES |
| Length of the product unit | 0.11 |
| Width of the product unit | 0.106 |
| Depth of the product unit | 0.076 |
| Weight | 0.11 |
| ETIM - Electrical characteristics | |
| Nominal voltage [V] | 690 |
| Number of poles | 1 |
| Concurrently switching neutral conductor | No |
| ETIM - Mechanical characteristics | |
| Built-in depth [mm] | 49.5 |
| Degree of protection (IP) | IP2X |
| Mounting method | DIN rail |
| For fuse size | 14x51 mm |
| Width in number of modular spacings | 1 |
| ETIM - Technical features | |
| Lockable | Yes |
| With optical defect indication | Yes |
| Logistics | |
| GTIN/EAN | 3596031805969 |
| Customs number | 8536105090 |
| Price unit | PC |
| Weight of the packing unit | 0.11 |
| Length of the packing unit | 0.075 |
| Width of the packing unit | 0.03 |
| Depth of the packing unit | 0.11 |
| Norms | |
| Conformity to standards | IEC UL |
| Technical Characteristics | |
| Fuse melting indicator | Yes |
| Fuse size | 14x51 |
| Number of poles | 1 |
| Rated current | 50 |
| Size | RM/RMS 50 |