

57PV0L01

**Modular fuse holder for cylindrical fuses RM PV FUSE SWITCH
32A 1P**



Strong points

- Improved safety
- Product dedicated to PV UL and IEC applications
- Features and options

Compliance with standards

- IEC 60269
- UL 4248-18

Access to resources (ex: manuals)



<https://www.socomec.co.uk/en-gb/reference/57PV0L01>

RM PV are unipolar modular fuse disconnectors for gPV cylindrical fuses. They provide safety disconnection and protection against overcurrents caused by the reverse current in DC electrical PV circuits. RM PVs are fuse disconnect switches with or without light signalling for fuses without strikers.

Technical Characteristics

Height [mm]	78
Width [mm]	58
Depth [mm]	17.5
Weight [kg]	0.06
Fuse melting indicator	Yes
Fuse size	10x38
Number of poles	1
Rated current [A]	32
Size	RM32

Classification

UNSPSC	39121624
ETIM Class	EC002705
IGCC	4974

Commerce

Effective date	2014-07-09
Offer Life Cycle Code	40
Country of origin	ES

Logistics

GTIN/EAN	3596032814366
Customs number	8536105090
Price unit	PC
Weight of the packing unit [kg]	0.06
Length of the packing unit [m]	0.085
Width of the packing unit [m]	0.065
Depth of the packing unit [m]	0.02

Norms

Conformity to standards	IEC UL
-------------------------	------------