

60190000

Solid cylindrical link 10x38 32A max



Conducting piece to fit the neutral pole of cylindrical fused disconnecting switches.

Classification

| | |
|------------|----------|
| UNSPSC | 39121609 |
| ETIM Class | EC000026 |
| IGCC | 4905 |

Commerce

| | |
|----------------------------|------------|
| Effective date | 1988-04-15 |
| Country of origin | ES |
| Length of the product unit | 0.038 |
| Width of the product unit | 0.0103 |
| Weight | 0.01 |

ETIM - Electrical characteristics

| | |
|-------------------|----|
| Rated current [A] | 32 |
|-------------------|----|

ETIM - Mechanical characteristics

| | |
|-------------------|-------|
| Construction size | Other |
|-------------------|-------|

Logistics

| | |
|----------------------------|---------------|
| GTIN/EAN | 3596031377336 |
| Customs number | 7419809099 |
| Price unit | PC |
| Weight of the packing unit | 0.01 |
| Length of the packing unit | 0.04 |
| Width of the packing unit | 0.01 |
| Depth of the packing unit | 0.01 |

Norms

| | |
|-------------------------|-----|
| Conformity to standards | IEC |
|-------------------------|-----|

Technical Characteristics

| | |
|------------------------|-----------------|
| Fuse melting indicator | without striker |
| Rated voltage | 415 VAC |
| Rated current | 32 |
| Type | 10x38 |

General characteristics

- 3 sizes: 10 x 38, 14 x 51, 22 x 58.

Access to resources (ex: manuals)

<https://www.socomec.co.uk/en-gb/reference/60190000>