

**60630025**

## Cylindrical fuse with striker aM type 22x58 690Vac 25A



### Strong points

- High-performance
- Increased reliability
- Improved safety

### General characteristics

- High-performance.
- High level of reliability.
- Improved safety.

### Compliance with standards

- IEC 60269-1
- IEC 60269-2

### Access to resources (ex: manuals)

<https://www.socomec.co.uk/en-gb/reference/60630025>

Industrial fuses protect installations and people from overcurrents for any low voltage electrical circuit.

|  |                            |
|--|----------------------------|
| <b>Classification</b>                    |                            |
| UNSPSC                                   | 39121609                   |
| ETIM Class                               | EC002704                   |
| IGCC                                     | 4905                       |
| <b>Commerce</b>                          |                            |
| Effective date                           | 1988-04-15                 |
| Country of origin                        | ES                         |
| Length of the product unit               | 0.051                      |
| Width of the product unit                | 0.0143                     |
| Weight                                   | 0.05                       |
| <b>ETIM - Electrical characteristics</b> |                            |
| Voltage type                             | AC                         |
| Rated current [A]                        | 25                         |
| Rated voltage [V]                        | 690                        |
| Utilization category                     | aM (switchgear protection) |
| Rated operating frequency [Hz]           | 50..60                     |
| <b>ETIM - Mechanical characteristics</b> |                            |
| Size                                     | 14x51 mm                   |
| Type of fuse status indicator            | Top fuse status indicator  |
| <b>ETIM - Technical features</b>         |                            |
| Model                                    | Ceramic fuse               |
| <b>Logistics</b>                         |                            |
| GTIN/EAN                                 | 3596031378708              |
| Customs number                           | 8536105090                 |
| Price unit                               | PC                         |
| Weight of the packing unit               | 0.05                       |
| Length of the packing unit               | 0.02                       |
| Width of the packing unit                | 0.02                       |
| Depth of the packing unit                | 0.06                       |
| <b>Norms</b>                             |                            |
| Conformity to standards                  | IEC                        |
| <b>Technical Characteristics</b>         |                            |
| Fuse melting indicator                   | with striker               |
| Fuse size                                | 22x58                      |
| Rated voltage                            | 690 VAC                    |
| Rated current                            | 25                         |
| Type                                     | aM                         |