

60630100

Cylindrical fuse with striker aM type 22x58 400Vac 100A



Strong points

- High-performance
- Increased reliability
- Improved safety

General characteristics

- High-performance.
- High level of reliability.
- Improved safety.

Compliance with standards

- IEC 60269-1
- IEC 60269-2

Access to resources (ex: manuals)

<https://www.socomec.co.uk/en-gb/reference/60630100>

Industrial fuses protect installations and people from overcurrents for any low voltage electrical circuit.

| | |
|--|----------------------------|
| Classification | |
| UNSPSC | 39121609 |
| ETIM Class | EC002704 |
| IGCC | 4905 |
| Commerce | |
| Effective date | 1988-04-15 |
| Country of origin | ES |
| Length of the product unit | 0.051 |
| Width of the product unit | 0.0143 |
| Weight | 0.05 |
| ETIM - Electrical characteristics | |
| Voltage type | AC |
| Rated current [A] | 100 |
| Rated voltage [V] | 690 |
| Utilization category | aM (switchgear protection) |
| Rated operating frequency [Hz] | 50..60 |
| ETIM - Mechanical characteristics | |
| Size | 14x51 mm |
| Type of fuse status indicator | Top fuse status indicator |
| ETIM - Technical features | |
| Model | Ceramic fuse |
| Logistics | |
| GTIN/EAN | 3596031378760 |
| Customs number | 8536109090 |
| Price unit | PC |
| Weight of the packing unit | 0.05 |
| Length of the packing unit | 0.02 |
| Width of the packing unit | 0.02 |
| Depth of the packing unit | 0.06 |
| Norms | |
| Conformity to standards | IEC |
| Technical Characteristics | |
| Fuse melting indicator | with striker |
| Fuse size | 22x58 |
| Rated voltage | 400 VAC |
| Rated current | 100 |
| Type | aM |