


64200000

NFC/DIN industrial fuses DIN Solid Link 160A 415 VAC



Solid link to be used in conjunction with fuse bases or knife-edge fused disconnecting switches, generally fitted on the neutral pole.

General characteristics

- 6 sizes: 000/00C/00-0-1-2-3-4.

Access to resources (ex: manuals)



<https://www.socomec.co.uk/en-gb/reference/64200000>

Technical Characteristics

Height [mm]	48
Width [mm]	80
Depth [mm]	30
Weight [kg]	0.08
Fuse melting indicator	without striker
Rated voltage	415 VAC
Rated current [A]	160
Type	NH00

Classification

UNSPSC	39121612
ETIM Class	EC000026
IGCC	4908

Commerce

Effective date	1988-04-15
Offer Life Cycle Code	40
Country of origin	FR

ETIM - Electrical characteristics

Rated current [A]	160
-------------------	-----

ETIM - Mechanical characteristics

Construction size	NH00
-------------------	------

Logistics

GTIN/EAN	3596031381456
Customs number	8538909999
Price unit	PC
Weight of the packing unit [kg]	0.08
Length of the packing unit [m]	0.08
Width of the packing unit [m]	0.05
Depth of the packing unit [m]	0.023

Norms

Conformity to standards	IEC
-------------------------	-----