

68530040

Knife-edge fuse with striker aM type NH S0 690Vac 40A



Strong points

- High-performance
- Increased reliability
- Improved safety

General characteristics

- High-performance.
- High level of reliability.
- Improved safety.

Compliance with standards

- IEC 60269-1
- IEC 60269-2

Access to resources (ex: manuals)

<https://www.socomec.co.uk/en-gb/reference/68530040>

Socomec industrial fuses protect installations and people from overcurrents for low voltage electrical circuits.

| | |
|---|----------------------------|
| Classification | |
| UNSPSC | 39121612 |
| ETIM Class | EC000055 |
| IGCC | 4908 |
| Commerce | |
| Effective date | 1988-04-15 |
| Obsolescence date | 2021-09-01 |
| Production ban date | 2022-02-01 |
| Country of origin | ES |
| Length of the product unit | 0.048 |
| Width of the product unit | 0.1275 |
| Depth of the product unit | 0.045 |
| Weight | 0.296 |
| ETIM - Electrical characteristics | |
| Voltage type | AC |
| Rated current [A] | 40 |
| Rated voltage AC [V] | 690 |
| Utilization category | aM (switchgear protection) |
| ETIM - Technical features | |
| Fuse construction type according to IEC 60269 | NH0 |
| Logistics | |
| GTIN/EAN | 3596031408160 |
| Customs number | 8536105090 |
| Price unit | PC |
| Weight of the packing unit | 0.296 |
| Length of the packing unit | 0.055 |
| Width of the packing unit | 0.04 |
| Depth of the packing unit | 0.12 |
| Norms | |
| Conformity to standards | IEC |
| Technical Characteristics | |
| Fuse melting indicator | with striker |
| Fuse size | S0 |
| Rated voltage | 690 VAC |
| Rated current | 40 |
| Type | aM |