

68530100

Knife-edge fuse with striker aM type NH S0 690Vac 100A



Strong points

- High-performance
- Increased reliability
- Improved safety

General characteristics

- High-performance.
- High level of reliability.
- Improved safety.

Compliance with standards

- IEC 60269-1
- IEC 60269-2

Access to resources (ex: manuals)

2024-05-19 04:29:43



https://www.socomec.co.uk/engb/reference/68530100

Socomec industrial fuses protect installations and people from overcurrents for low voltage electrical circuits.

NSPSC	39121612
ETIM Class	EC000055
GCC	4908
Commerce	
Effective date	1988-04-15
Country of origin	ES
ength of the product unit	0.048
Nidth of the product unit	0.1275
Depth of the product unit	0.045
Veight	0.32
ETIM - Electrical characteristics	
Voltage type	AC
Rated current [A]	100
Rated voltage AC [V]	690
Jtilization category	aM (switchgear protection)
ETIM - Technical features	
Fuse construction type according to IEC 60269	NH0
Logistics	
GTIN/EAN	3596031408207
Customs number	8536109090
Price unit	PC
Weight of the packing unit	0.32
ength of the packing unit	0.13
Nidth of the packing unit	0.04
Depth of the packing unit	0.05
Norms	
Conformity to standards	IEC
Technical Characteristics	
Fuse melting indicator	with striker
Fuse size	S0
Rated voltage	690 VAC
Rated current	100
Гуре	aM

2024-05-19 04:29:43 2/2