

**68530125**

## Knife-edge fuse with striker aM type NH S0 690Vac 125A



### Strong points

- High-performance
- Increased reliability
- Improved safety

### General characteristics

- High-performance.
- High level of reliability.
- Improved safety.

### Compliance with standards

- IEC 60269-1
- IEC 60269-2

### Access to resources (ex: manuals)

<https://www.socomec.co.uk/en-gb/reference/68530125>

Socomec industrial fuses protect installations and people from overcurrents for low voltage electrical circuits.

<b>Classification</b>	
UNSPSC	39121612
ETIM Class	EC000055
IGCC	4908
<b>Commerce</b>	
Effective date	1988-04-15
Country of origin	ES
Length of the product unit	0.048
Width of the product unit	0.1275
Depth of the product unit	0.045
Weight	0.319
<b>ETIM - Electrical characteristics</b>	
Voltage type	AC
Rated current [A]	125
Rated voltage AC [V]	690
Utilization category	aM (switchgear protection)
<b>ETIM - Technical features</b>	
Fuse construction type according to IEC 60269	NH0
<b>Logistics</b>	
GTIN/EAN	3596031408214
Customs number	8536109090
Price unit	PC
Weight of the packing unit	0.319
Length of the packing unit	0.125
Width of the packing unit	0.042
Depth of the packing unit	0.06
<b>Norms</b>	
Conformity to standards	IEC
<b>Technical Characteristics</b>	
Fuse melting indicator	with striker
Fuse size	S0
Rated voltage	690 VAC
Rated current	125
Type	aM