

68630125

Knife-edge fuse with striker aM type NH S1 690Vac 125A



Strong points

- High-performance
- Increased reliability
- Improved safety

General characteristics

- High-performance.
- High level of reliability.
- Improved safety.

Compliance with standards

- IEC 60269-1
- IEC 60269-2

Access to resources (ex: manuals)

2024-05-12 05:42:42



https://www.socomec.co.uk/engb/reference/68630125

Socomec industrial fuses protect installations and people from overcurrents for low voltage electrical circuits.

| NSPSC | 39121612 |
|---|----------------------------|
| ETIM Class | EC000055 |
| GCC | 4908 |
| Commerce | |
| Effective date | 1988-04-15 |
| Country of origin | ES |
| ength of the product unit | 0.053 |
| Nidth of the product unit | 0.1375 |
| Depth of the product unit | 0.052 |
| Veight | 0.36 |
| ETIM - Electrical characteristics | |
| /oltage type | AC |
| Rated current [A] | 125 |
| Rated voltage AC [V] | 690 |
| Jtilization category | aM (switchgear protection) |
| ETIM - Technical features | |
| Fuse construction type according to IEC 60269 | NH1 |
| ogistics | |
| GTIN/EAN | 3596031408405 |
| Customs number | 8536109090 |
| Price unit | PC |
| Weight of the packing unit | 0.36 |
| ength of the packing unit | 0.069 |
| Nidth of the packing unit | 0.138 |
| Depth of the packing unit | 0.146 |
| Norms | |
| Conformity to standards | IEC |
| Technical Characteristics | |
| Fuse melting indicator | with striker |
| Fuse size | S1 |
| Rated voltage | 690 VAC |
| Rated current | 125 |
| Гуре | aM |

2024-05-12 05:42:42 2/2