

68630160

Knife-edge fuse with striker aM type NH S1 690Vac 160A



Strong points

- High-performance
- Increased reliability
- Improved safety

General characteristics

- High-performance.
- High level of reliability.
- Improved safety.

Compliance with standards

- IEC 60269-1
- IEC 60269-2

Access to resources (ex: manuals)

2024-05-13 18:28:26



https://www.socomec.co.uk/engb/reference/68630160

Socomec industrial fuses protect installations and people from overcurrents for low voltage electrical circuits.

NSPSC	39121612
ETIM Class	EC000055
GCC	4908
Commerce	
Effective date	1988-04-15
Country of origin	ES
ength of the product unit	0.053
Nidth of the product unit	0.1375
Depth of the product unit	0.052
Veight	0.396
ETIM - Electrical characteristics	
Voltage type	AC
Rated current [A]	160
Rated voltage AC [V]	690
Jtilization category	aM (switchgear protection)
ETIM - Technical features	
Fuse construction type according to IEC 60269	NH1
Logistics	
GTIN/EAN	3596031408412
Customs number	8536109090
Price unit	PC
Weight of the packing unit	0.396
ength of the packing unit	0.135
Nidth of the packing unit	0.04
Depth of the packing unit	0.065
Norms	
Conformity to standards	IEC
Technical Characteristics	
Fuse melting indicator	with striker
Fuse size	S1
Rated voltage	690 VAC
Rated current	160
Гуре	aM

2024-05-13 18:28:27 2/2