

**6A200006**
**BS88 gG 6A 550Vac 80kA fuselink size A2, offset bolted tag type AAO**
**Strong points**

- High-performance
- Increased reliability
- Safety

**General characteristics**

- High level performance.
- High reliability.
- Safety.

**Compliance with standards**

- IEC 60269-1
- IEC 60269-2
- IEC 60269-2-1
- NF EN 60269-1
- NF C 63-210
- NF C 63211
- VDE 0636-10
- DIN 43620

**Access to resources (ex: manuals)**

Socomec industrial fuses protect installations and people from overcurrents for low voltage electrical circuits.

**Classification**

UNSPSC	39121612
ETIM Class	EC000055
IGCC	4908

**Commerce**

Effective date	1998-03-16
Country of origin	IN

**ETIM - Electrical characteristics**

Voltage type	AC
Rated current [A]	6
Rated voltage AC [V]	550
Utilization category	Other

**ETIM - Mechanical characteristics**

Type of fuse status indicator	None
-------------------------------	------

**ETIM - Technical features**

Fuse construction type according to IEC 60269	Other
---	-------

**Logistics**

GTIN/EAN	3596031419029
Customs number	8536101090
Price unit	PC
Weight of the packing unit	0.06

**Norms**

Conformity to standards	IEC
-------------------------	-----

**Technical Characteristics**

Fuse melting indicator	without striker
Fuse size	A2
Rated voltage	550 VAC
Rated current	6
Type	gG

<https://www.socomec.co.uk/en-gb/reference/6A200006>