

6A200010
BS88 gG 10A 550Vac 80kA fuselink size A2, offset bolted tag type AAO
Strong points

- High-performance
- Increased reliability
- Safety

General characteristics

- High level performance.
- High reliability.
- Safety.

Compliance with standards

- IEC 60269-1
- IEC 60269-2
- IEC 60269-2-1
- NF EN 60269-1
- NF C 63-210
- NF C 63211
- VDE 0636-10
- DIN 43620

Access to resources (ex: manuals)

Socomec industrial fuses protect installations and people from overcurrents for low voltage electrical circuits.

Classification

UNSPSC	39121612
ETIM Class	EC000055
IGCC	4908

Commerce

Effective date	1998-03-16
Country of origin	IN

ETIM - Electrical characteristics

Voltage type	AC
Rated current [A]	10
Rated voltage AC [V]	550
Utilization category	Other

ETIM - Mechanical characteristics

Type of fuse status indicator	None
-------------------------------	------

ETIM - Technical features

Fuse construction type according to IEC 60269	Other
---	-------

Logistics

GTIN/EAN	3596031419036
Customs number	8536101090
Price unit	PC
Weight of the packing unit	0.06

Norms

Conformity to standards	IEC
-------------------------	-----

Technical Characteristics

Fuse melting indicator	without striker
Fuse size	A2
Rated voltage	550 VAC
Rated current	10
Type	gG

<https://www.socomec.co.uk/en-gb/reference/6A200010>