

**6A2M0063**
**BS88 gM 32/63A 500Vac 80kA fuselink size A2, offset bolted tag type AAO**
**Strong points**

- High-performance
- Increased reliability
- Safety

**General characteristics**

- High level performance.
- High reliability.
- Safety.

**Compliance with standards**

- IEC 60269-1
- IEC 60269-2
- IEC 60269-2-1
- NF EN 60269-1
- NF C 63-210
- NF C 63211
- VDE 0636-10
- DIN 43620

**Access to resources (ex: manuals)**

Socomec industrial fuses protect installations and people from overcurrents for low voltage electrical circuits.

**Classification**

UNSPSC	39121612
ETIM Class	EC000055
IGCC	4908

**Commerce**

Effective date	1998-03-26
Country of origin	IN

**ETIM - Electrical characteristics**

Voltage type	AC
Rated current [A]	32
Rated voltage AC [V]	500
Utilization category	Other

**ETIM - Mechanical characteristics**

Type of fuse status indicator	None
-------------------------------	------

**ETIM - Technical features**

Fuse construction type according to IEC 60269	Other
---	-------

**Logistics**

GTIN/EAN	3596031419111
Customs number	8536105090
Price unit	PC
Weight of the packing unit	45
Length of the packing unit	0.85
Width of the packing unit	0.02
Depth of the packing unit	0.025

**Norms**

Conformity to standards	IEC
-------------------------	-----

**Technical Characteristics**

Fuse melting indicator	without striker
Fuse size	A2
Rated voltage	500 VAC
Rated current	32..63
Type	gM

<https://www.socomec.co.uk/en-gb/reference/6A2M0063>