

## 6A300050

# BS88 gG 50A 500Vac 80kA fuselink size A3, offset bolted tag type BAO

### Strong points

- High-performance
- Increased reliability
- Safety

### General characteristics

- High level performance.
- High reliability.
- Safety.

### Compliance with standards

- IEC 60269-1
- IEC 60269-2
- IEC 60269-2-1
- NF EN 60269-1
- NF C 63-210
- NF C 63211
- VDE 0636-10
- DIN 43620

### Access to resources (ex: manuals)

Socomec industrial fuses protect installations and people from overcurrents for low voltage electrical circuits.

### Classification

UNSPSC	39121612
ETIM Class	EC000055
IGCC	4908

### Commerce

Effective date	1998-03-26
Country of origin	IN

### ETIM - Electrical characteristics

Voltage type	AC
Rated current [A]	50
Rated voltage AC [V]	500
Utilization category	Other

### ETIM - Mechanical characteristics

Type of fuse status indicator	None
-------------------------------	------

### ETIM - Technical features

Fuse construction type according to IEC 60269	Other
---	-------

### Logistics

GTIN/EAN	3596031419135
Customs number	8536105090
Price unit	PC
Weight of the packing unit	0.05
Length of the packing unit	0.022
Width of the packing unit	0.02
Depth of the packing unit	0.085

### Norms

Conformity to standards	IEC
-------------------------	-----

### Technical Characteristics

Fuse melting indicator	without striker
Fuse size	A3
Rated voltage	500 VAC
Rated current	50
Type	gG

<https://www.socomec.co.uk/en-gb/reference/6A300050>