

6A400160
BS88 gG 160A 415Vac 80kA fuselink size A4, offset bolted tag type DEO
Strong points

- High-performance
- Increased reliability
- Safety

General characteristics

- High level performance.
- High reliability.
- Safety.

Compliance with standards

- IEC 60269-1
- IEC 60269-2
- IEC 60269-2-1
- NF EN 60269-1
- NF C 63-210
- NF C 63211
- VDE 0636-10
- DIN 43620

Access to resources (ex: manuals)

Socomec industrial fuses protect installations and people from overcurrents for low voltage electrical circuits.

Classification

| | |
|------------|----------|
| UNSPSC | 39121612 |
| ETIM Class | EC000055 |
| IGCC | 4908 |

Commerce

| | |
|-------------------|------------|
| Effective date | 1998-03-26 |
| Country of origin | IN |

ETIM - Electrical characteristics

| | |
|----------------------|-------|
| Voltage type | AC |
| Rated current [A] | 160 |
| Rated voltage AC [V] | 415 |
| Utilization category | Other |

ETIM - Mechanical characteristics

| | |
|-------------------------------|------|
| Type of fuse status indicator | None |
|-------------------------------|------|

ETIM - Technical features

| | |
|---|-------|
| Fuse construction type according to IEC 60269 | Other |
|---|-------|

Logistics

| | |
|----------------------------|---------------|
| GTIN/EAN | 3596031419289 |
| Customs number | 8536109090 |
| Price unit | PC |
| Weight of the packing unit | 0.14 |
| Length of the packing unit | 0.12 |
| Width of the packing unit | 0.04 |
| Depth of the packing unit | 0.045 |

Norms

| | |
|-------------------------|-----|
| Conformity to standards | IEC |
|-------------------------|-----|

Technical Characteristics

| | |
|------------------------|-----------------|
| Fuse melting indicator | without striker |
| Fuse size | A4 |
| Rated voltage | 415 VAC |
| Rated current | 160 |
| Type | gG |

<https://www.socomec.co.uk/en-gb/reference/6A400160>