

## 6A4M0125

# BS88 gM 100/125A 415Vac 80kA fuselink size A4, offset bolted tag type CEO

### Strong points

- High-performance
- Increased reliability
- Safety

### General characteristics

- High level performance.
- High reliability.
- Safety.

### Compliance with standards

- IEC 60269-1
- IEC 60269-2
- IEC 60269-2-1
- NF EN 60269-1
- NF C 63-210
- NF C 63211
- VDE 0636-10
- DIN 43620

### Access to resources (ex: manuals)

Socomec industrial fuses protect installations and people from overcurrents for low voltage electrical circuits.

### Classification

UNSPSC	39121612
ETIM Class	EC000055
IGCC	4908

### Commerce

Effective date	1998-03-26
Country of origin	HU

### ETIM - Electrical characteristics

Voltage type	AC
Rated current [A]	100
Rated voltage AC [V]	415
Utilization category	Other

### ETIM - Mechanical characteristics

Type of fuse status indicator	None
-------------------------------	------

### ETIM - Technical features

Fuse construction type according to IEC 60269	Other
---	-------

### Logistics

GTIN/EAN	3596031419302
Customs number	8536109090
Price unit	PC
Weight of the packing unit	0.1
Length of the packing unit	0.028
Width of the packing unit	0.025
Depth of the packing unit	0.11

### Norms

Conformity to standards	IEC
-------------------------	-----

### Technical Characteristics

Fuse melting indicator	without striker
Fuse size	A4
Rated voltage	415 VAC
Rated current	100..125
Type	gM

<https://www.socomec.co.uk/en-gb/reference/6A4M0125>