

**6B100025**

## BS88 gG 25A 550Vac 80kA fuselink size B1, center bolted tag type AD

### Strong points

- High-performance
- Increased reliability
- Safety

### General characteristics

- High level performance.
- High reliability.
- Safety.

### Compliance with standards

- IEC 60269-1
- IEC 60269-2
- IEC 60269-2-1
- NF EN 60269-1
- NF C 63-210
- NF C 63211
- VDE 0636-10
- DIN 43620

### Access to resources (ex: manuals)

Socomec industrial fuses protect installations and people from overcurrents for low voltage electrical circuits.

### Classification

UNSPSC	39121612
ETIM Class	EC000055
IGCC	4908

### Commerce

Effective date	1998-03-26
Country of origin	IN

### ETIM - Electrical characteristics

Voltage type	AC
Rated current [A]	25
Rated voltage AC [V]	550
Utilization category	Other

### ETIM - Mechanical characteristics

Type of fuse status indicator	None
-------------------------------	------

### ETIM - Technical features

Fuse construction type according to IEC 60269	Other
---	-------

### Logistics

GTIN/EAN	3596031419418
Customs number	8536105090
Price unit	PC
Weight of the packing unit	0.1

### Norms

Conformity to standards	IEC
-------------------------	-----

### Technical Characteristics

Fuse melting indicator	without striker
Fuse size	B1
Rated voltage	550 VAC
Rated current	25
Type	gG

<https://www.socomec.co.uk/en-gb/reference/6B100025>