

6B100032

BS88 gG 32A 550Vac 80kA fuselink size B1, center bolted tag type AD

Strong points

- High-performance
- Increased reliability
- Safety

General characteristics

- High level performance.
- High reliability.
- Safety.

Compliance with standards

- IEC 60269-1
- IEC 60269-2
- IEC 60269-2-1
- NF EN 60269-1
- NF C 63-210
- NF C 63211
- VDE 0636-10
- DIN 43620

Access to resources (ex: manuals)

Socomec industrial fuses protect installations and people from overcurrents for low voltage electrical circuits.

Classification

UNSPSC	39121612
ETIM Class	EC000055
IGCC	4908

Commerce

Effective date	1998-03-26
Country of origin	IN

ETIM - Electrical characteristics

Voltage type	AC
Rated current [A]	32
Rated voltage AC [V]	550
Utilization category	Other

ETIM - Mechanical characteristics

Type of fuse status indicator	None
-------------------------------	------

ETIM - Technical features

Fuse construction type according to IEC 60269	Other
---	-------

Logistics

GTIN/EAN	3596031419425
Customs number	8536105090
Price unit	PC
Weight of the packing unit	0.06

Norms

Conformity to standards	IEC
-------------------------	-----

Technical Characteristics

Fuse melting indicator	without striker
Fuse size	B1
Rated voltage	550 VAC
Rated current	32
Type	gG

<https://www.socomec.co.uk/en-gb/reference/6B100032>