

**6B2M0250**
**BS88 gM 200/250A 415Vac 80kA fuselink size B2, center bolted tag type DD**
**Strong points**

- High-performance
- Increased reliability
- Safety

**General characteristics**

- High level performance.
- High reliability.
- Safety.

**Compliance with standards**

- IEC 60269-1
- IEC 60269-2
- IEC 60269-2-1
- NF EN 60269-1
- NF C 63-210
- NF C 63211
- VDE 0636-10
- DIN 43620

**Access to resources (ex: manuals)**

Socomec industrial fuses protect installations and people from overcurrents for low voltage electrical circuits.

**Classification**

UNSPSC	39121612
ETIM Class	EC000055
IGCC	4908

**Commerce**

Effective date	1998-03-27
Country of origin	IN

**ETIM - Electrical characteristics**

Voltage type	AC
Rated current [A]	200
Rated voltage AC [V]	415
Utilization category	Other

**ETIM - Mechanical characteristics**

Type of fuse status indicator	None
-------------------------------	------

**ETIM - Technical features**

Fuse construction type according to IEC 60269	Other
---	-------

**Logistics**

GTIN/EAN	3596031419548
Customs number	8536109090
Price unit	PC
Weight of the packing unit	0.736
Length of the packing unit	0.032
Width of the packing unit	0.14
Depth of the packing unit	0.155

**Norms**

Conformity to standards	IEC
-------------------------	-----

**Technical Characteristics**

Fuse melting indicator	without striker
Fuse size	B2
Rated voltage	415 VAC
Rated current	200..250
Type	gM

<https://www.socomec.co.uk/en-gb/reference/6B2M0250>