

6F1M0063
BS88 gM 32/63A 415Vac 80kA fuselink size F1, solid blade tag type NSD
Strong points

- High-performance
- Increased reliability
- Safety

General characteristics

- High level performance.
- High reliability.
- Safety.

Compliance with standards

- IEC 60269-1
- IEC 60269-2
- IEC 60269-2-1
- NF EN 60269-1
- NF C 63-210
- NF C 63211
- VDE 0636-10
- DIN 43620

Access to resources (ex: manuals)

Socomec industrial fuses protect installations and people from overcurrents for low voltage electrical circuits.

Classification

| | |
|------------|----------|
| UNSPSC | 39121612 |
| ETIM Class | EC000055 |
| IGCC | 4908 |

Commerce

| | |
|---------------------|------------|
| Effective date | 1998-03-30 |
| Obsolescence date | 2021-07-31 |
| Production ban date | 2021-12-31 |
| Country of origin | GB |

ETIM - Electrical characteristics

| | |
|----------------------|-------|
| Voltage type | AC |
| Rated current [A] | 32 |
| Rated voltage AC [V] | 415 |
| Utilization category | Other |

ETIM - Mechanical characteristics

| | |
|-------------------------------|------|
| Type of fuse status indicator | None |
|-------------------------------|------|

ETIM - Technical features

| | |
|---|-------|
| Fuse construction type according to IEC 60269 | Other |
|---|-------|

Logistics

| | |
|----------------------------|---------------|
| GTIN/EAN | 3596031420117 |
| Customs number | 8536105090 |
| Price unit | PC |
| Weight of the packing unit | 0.1 |

Norms

| | |
|-------------------------|-----|
| Conformity to standards | IEC |
|-------------------------|-----|

Technical Characteristics

| | |
|------------------------|-----------------|
| Fuse melting indicator | without striker |
| Fuse size | F1 |
| Rated voltage | 415 VAC |
| Rated current | 63..80 |
| Type | gM |

<https://www.socomec.co.uk/en-gb/reference/6F1M0063>