

6F2M0100
BS88 gM 63/100A 415Vac 80kA fuselink size F2, solid blade tag type ESD
Strong points

- High-performance
- Increased reliability
- Safety

General characteristics

- High level performance.
- High reliability.
- Safety.

Compliance with standards

- IEC 60269-1
- IEC 60269-2
- IEC 60269-2-1
- NF EN 60269-1
- NF C 63-210
- NF C 63211
- VDE 0636-10
- DIN 43620

Access to resources (ex: manuals)

Socomec industrial fuses protect installations and people from overcurrents for low voltage electrical circuits.

Classification

UNSPSC	39121612
ETIM Class	EC000055
IGCC	4908

Commerce

Effective date	1998-03-30
Obsolescence date	2021-07-31
Production ban date	2021-12-31
Country of origin	GB

ETIM - Electrical characteristics

Voltage type	AC
Rated current [A]	63
Rated voltage AC [V]	415
Utilization category	Other

ETIM - Mechanical characteristics

Type of fuse status indicator	None
-------------------------------	------

ETIM - Technical features

Fuse construction type according to IEC 60269	Other
---	-------

Logistics

GTIN/EAN	3596031420247
Customs number	8536109090
Price unit	PC
Weight of the packing unit	0.1

Norms

Conformity to standards	IEC
-------------------------	-----

Technical Characteristics

Fuse melting indicator	without striker
Fuse size	F2
Rated voltage	415 VAC
Rated current	63..100
Type	gM

<https://www.socomec.co.uk/en-gb/reference/6F2M0100>