

**86P02031**

## DC LOAD BREAK SWITCH INOSYS LBS MANUEL IEC 315A 2P 1000VDC F2



### Strong points

- High performance power switching in a compact frame
- Safe and reliable operation
- Designed for harsh environments
- Easy to install
- Modular solution for flexible configuration

### General characteristics

- Range 160 A to 1600 A.
- Up to 2000 VDC.
- High-performance switching with a compact design.
- Easy integration.
- Reinforced safety with visible breaking indication.
- High efficiency with low power loss.

### Compliance with standards

- IEC 60947-3
- DC-21B & DC-PV2
- CCC

### Access to resources (ex: manuals)



<https://www.socomec.co.uk/en-gb/reference/86P02031>

INOSYS is a range of load break switches that can be controlled manually, by using the handle to disconnect all or part of the electrical installation. They ensure on-load opening / closing and safe disconnection of any direct current low voltage electrical circuit up to 2000 VDC. They can also be used for emergency power switching applications. They are the first switches on the market capable of handling 2000 VDC.

<b>Classification</b>	
UNSPSC	39122233
ETIM Class	EC000216
IGCC	5290
<b>Commerce</b>	
Effective date	2015-10-06
Country of origin	TN
Length of the product unit	0.154
Width of the product unit	0.117
Depth of the product unit	0.11
Weight	0.01
<b>ETIM - Electrical characteristics</b>	
Max. rated operation voltage Ue AC [V]	1500
Rated operating voltage [V]	600..1000
Rated permanent current Iu [A]	315
Rated short-time withstand current Icw [kA]	5
Number of poles	2
<b>ETIM - Mechanical characteristics</b>	
Suitable for floor mounting	No
Suitable for front mounting 4-hole	Yes
Suitable for front mounting centre	No
Suitable for distribution board installation	Yes
Suitable for intermediate mounting	Yes
Colour control element	Other
Degree of protection (IP), front side	IP20
<b>ETIM - Technical features</b>	
Version as main switch	Yes
Version as maintenance-/service switch	Yes
Version as safety switch	Yes
Version as emergency stop installation	Yes
Version as reversing switch	No
Number of switches	1
Motor drive optional	No
Motor drive integrated	No
Voltage release optional	No
Device construction	Built-in device fixed built-in technique
Type of control element	Other
Interlockable	Yes
Type of electrical connection of main circuit	Bolt connection
<b>Logistics</b>	
GTIN/EAN	3596032929183
Customs number	8536508090



Price unit	PC
Weight of the packing unit	0.01
Length of the packing unit	0.385
Width of the packing unit	0.21
Depth of the packing unit	0.17
<b>Norms</b>	
Conformity to standards	CCC IEC
<b>Technical Characteristics</b>	
Control operator	Direct : E2 / External : S2
Number of poles	2
Rated voltage	1000
Rated current	315
Type	Frontal or lateral operation
Frame size	F2