

ITY2-EX100B

BATTERY MICRO ITYS 6-10KVA EBM 2 STR 240V



Strong points

- Total protection during downtime
- Easy installation and maintenance
- Electrical protection coordination for your safety

General characteristics

- Standard degree of protection: IP20.
- Optional degree of protection: IP32.
- Operating temperature: 0÷40 °C (+15 ÷ +25 °C recommended for long battery life).
- Ambient storage and transport temperature: -5 °C ÷ +40 °C max (recommended: 25 °C).
- Relative humidity (condensation-free): up to 95%.
- Product declaration: CE.

Compliance with standards

- CE
- EN 62040-1

Access to resources (ex: manuals)

<https://www.socomec.co.uk/en-gb/reference/ITY2-EX100B>

VRLA (Valve Regulated Lead Acid) batteries are lead batteries with a sealed safety valve container for releasing excess gas in the event of internal overpressure. Their development was aimed at limiting the emission of hydrogen into the atmosphere and to avoid the use of liquid electrolyte. The liquid electrolyte is replaced by gel electrolyte (GEL technology) or absorbed inside the separators (AGM technology) to prevent acid leaking.

Sealed batteries do not allow for water to be added to the electrolyte, therefore the evaporation of the water contained in the electrolyte, due for example to high room temperatures or internal heating as a result of charging/discharging cycles, decreases their lifetime.

Classification

ETIM Class	EC002850
------------	----------

Commerce

Effective date	2013-09-01
Obsolescence date	2021-04-24
Production ban date	2021-04-24
Country of origin	CN
Length of the product unit	0.708
Width of the product unit	0.26
Depth of the product unit	0.55
Weight	129

Logistics

GTIN/EAN	8027122549592
Customs number	8507208090
Weight of the packing unit	129
Length of the packing unit	0.55
Width of the packing unit	0.26
Depth of the packing unit	0.708

Technical Characteristics

Depth	550
Height	708
In/out	1/1
Width	260
Sn	10
Rate (min)	6
Rate (max)	10