

NPE-0650

NETYS PE 650VA USB



Strong points

- Ideal and cost-effective protection for SOHO or POS applications
- Easy to use
- A solution for network power cuts and voltage fluctuations
- Simplified connection
- Protection for your data line

General characteristics

- Minitower case.
- Step Wave, AVR function (Automatic Voltage Regulation).
- Control panel with LCD display.
- LOCAL VIEW software for local UPS monitoring.
- NTP data line suppressor.
- Up to 6 UPS output sockets.

Compliance with standards

- IEC/EN 62040-1, IEC/EN 62040-2
- AS 62040.1.1, AS 62040.1.2, AS 62040.2
- CE
- RCM (E2376)

Access to resources (ex: manuals)

<https://www.socomec.co.uk/en-gb/reference/NPE-0650>

Protection for small office, personal or point-of-sale applications.

| Classification | |
|-----------------------------------|--|
| UNSPSC | 39121011 |
| ETIM Class | EC000382 |
| IGCC | 4149 |
| Commerce | |
| Description (240 char.) | NeTYS PE 650VA/360W 230V 50/60Hz BATTERY INCLUDED WITH AVR, STEPWAVE PLUGS PROTECTED RJ45, 1xUSB |
| Effective date | 2012-09-01 |
| Country of origin | CN |
| Length of the product unit | 0.145 |
| Width of the product unit | 0.1 |
| Depth of the product unit | 0.3 |
| Weight | 5.2 |
| ETIM - Electrical characteristics | |
| Input voltage [V] | 140..300 |
| Primary frequency [Hz] | 45..66 |
| Number of phases primary | 1 |
| Output voltage [V] | 230..230 |
| Secondary frequency [Hz] | 50..60 |
| Output effective power [W] | 360 |
| Output apparent power [VA] | 650 |
| Number of phases secondary | 1 |
| SNMP | Yes |
| Voltage type | AC |
| Output power factor | 0.6 |
| ETIM - Mechanical characteristics | |
| Height [mm] | 145 |
| Width [mm] | 100 |
| Depth [mm] | 300 |
| Weight [kg] | 5.2 |
| Construction type | Free standing model |
| Input connection | C14 |
| Number of output connections C13 | 4 |
| ETIM - Technical features | |
| USB interface | Yes |
| Bridging time full load [min] | 2 |
| Suitable for network-management | Yes |
| USV- technology | Line-interactive |
| Overall efficiency [%] | 98 |
| Efficiency in eco-mode [%] | 98 |
| Potential free switch contact | Yes |
| Auto shut down function | Yes |
| Logistics | |
| GTIN/EAN | 8027122515153 |
| Customs number | 8504409590 |

| | |
|----------------------------------|-------------------------------|
| Weight of the packing unit | 5.2 |
| Length of the packing unit | 0.3 |
| Width of the packing unit | 0.1 |
| Depth of the packing unit | 0.145 |
| Norms | |
| Conformity to standards | IEC |
| Technical Characteristics | |
| Depth | 300 |
| Height | 145 |
| In/out | 1/1 |
| Output voltage | 230 |
| Rated frequency | 50/50 |
| Width | 100 |
| Sn | 0.65 |
| Pn | 0.36 |
| Conf | M2 |
| Input voltage | 230 |
| Rate (min) | 0.65 |
| Rate (max) | 0.65 |
| Life Time | 03-05 |
| Configuration | Line-Interactive UPS with AVR |