

NPE-B600

NETYS PE 600VA BASIS



Strong points

- Ideal and cost-effective protection for SOHO or POS applications
- Easy to use
- A solution for network power cuts and voltage fluctuations
- Simplified connection
- Protection for your data line

General characteristics

- Minitower case.
- Step Wave, AVR function (Automatic Voltage Regulation).
- Control panel with LCD display.
- LOCAL VIEW software for local UPS monitoring.
- NTP data line suppressor.
- Up to 6 UPS output sockets.

Compliance with standards

- IEC/EN 62040-1, IEC/EN 62040-2
- AS 62040.1.1, AS 62040.1.2, AS 62040.2
- CE
- RCM (E2376)

Access to resources (ex: manuals)

<https://www.socomec.co.uk/en-gb/reference/NPE-B600>

Protection for small office, personal or point-of-sale applications.

Classification	
UNSPSC	39121011
ETIM Class	EC000382
IGCC	4149
Commerce	
Description (240 char.)	NeTYS PE 600VA/360W 230V 50/60Hz BATTERY INCLUDED WITH AVR, STEPWAVE BASIS VERSION
Effective date	2012-09-01
Country of origin	CN
Length of the product unit	0.145
Width of the product unit	0.1
Depth of the product unit	0.3
Weight	5
ETIM - Electrical characteristics	
Input voltage [V]	140..300
Primary frequency [Hz]	45..66
Number of phases primary	1
Output voltage [V]	230..230
Secondary frequency [Hz]	50..60
Output effective power [W]	360
Output apparent power [VA]	600
Number of phases secondary	1
SNMP	No
Voltage type	AC
Output power factor	0.6
ETIM - Mechanical characteristics	
Height [mm]	145
Width [mm]	100
Depth [mm]	300
Weight [kg]	5
Construction type	Free standing model
Input connection	C14
Number of output connections C13	4
ETIM - Technical features	
USB interface	No
Bridging time full load [min]	2
Suitable for network-management	No
USV- technology	Line-interactive
Overall efficiency [%]	98
Efficiency in eco-mode [%]	98
Potential free switch contact	No
Auto shut down function	No
Logistics	
GTIN/EAN	8027122515146
Customs number	8504409590
Weight of the packing unit	5

Length of the packing unit	0.3
Width of the packing unit	0.1
Depth of the packing unit	0.145
Norms	
Conformity to standards	IEC
Technical Characteristics	
Depth	300
Height	145
In/out	1/1
Output voltage	230
Rated frequency	50/50
Width	100
Sn	0.6
Pn	0.36
Conf	M2
Input voltage	230
Rate (min)	0.6
Rate (max)	0.6
Life Time	03-05
Configuration	Line-Interactive UPS with AVR