

## NRT2-U3300

# NETYS RT 3K3VA 230VAC+BAT



### Strong points

- Simple to install
- High protection and availability
- Certified performance
- Easy to use
- Extended and flexible back-up time

### General characteristics

- Rail kit.
- Embedded dry-contact interface (5000-11000 VA).
- Input mains switch breaker (5000-11000 VA).
- Connection for battery extension modules.
- Port for parallel operation (5000-11000 VA).
- Power off the UPS remotely.
- Internal temperature sensor.

### Compliance with standards

- IEC 62040-1
- IEC 62040-2
- IEC 62040-3
- AS 62040.1.1
- AS 62040.1.2
- AS 62040.2
- RCM (E2376)

### Access to resources (ex: manuals)

<https://www.socomec.co.uk/en-gb/reference/NRT2-U3300>

Complete and professional, NETYS RT is a single-phase rack-tower UPS ensuring protection and availability of IT infrastructure that meet both requirements of power reliability and installation flexibility.

<b>Classification</b>	
UNSPSC	39121011
ETIM Class	EC000382
IGCC	4149
<b>Commerce</b>	
Description (240 char.)	NeTYS RT 3300VA/2700W VFI UPS 1/1 WITH BATTERY INTEGRATED +RAILS
Effective date	2016-04-30
Country of origin	CN
Length of the product unit	0.089
Width of the product unit	0.44
Depth of the product unit	0.608
Weight	30
<b>ETIM - Electrical characteristics</b>	
Input voltage [V]	175..280
Primary frequency [Hz]	45..66
Number of phases primary	1
Output voltage [V]	200..240
Secondary frequency [Hz]	50..60
Output effective power [W]	2700
Output apparent power [VA]	3300
Number of phases secondary	1
SNMP	Yes
Voltage type	AC
Max. voltage distortion output (linear load) [%]	2
Output power factor	0.82
<b>ETIM - Mechanical characteristics</b>	
Height [mm]	440
Width [mm]	88.7
Depth [mm]	608
Weight [kg]	30
Construction type	482.6 mm (19 inch) device
Input connection	C20
Number of output connections C13	6
Number of output connections C19	1
<b>ETIM - Technical features</b>	
USB interface	No
Bridging time full load [min]	6.8
Suitable for network-management	Yes
USV- technology	Online
Overall efficiency [%]	93
Efficiency in eco-mode [%]	98
Potential free switch contact	Yes
Auto shut down function	Yes
<b>Logistics</b>	

GTIN/EAN	8027122601146
Customs number	8504409590
Weight of the packing unit	30
Length of the packing unit	0.608
Width of the packing unit	0.44
Depth of the packing unit	0.089
<b>Norms</b>	
Conformity to standards	IEC
<b>Technical Characteristics</b>	
Depth	608
Height	89
In/out	1/1
Output voltage	230
Rated frequency	50/50
Width	440
Sn	3.3
Pn	2.7
Conf	C1
Input voltage	230
Rate (min)	3.3
Rate (max)	3.3
Life Time	03-05
Typical Backup Time	7
Configuration	UPS Single Unit(s) with Bypass