

RETROFIT Line MID active energy meter dedicated to existing installations

Single-circuit metering, measurement & analvsis





Function

Existing sites, having been built before optimised energy consumption was a consideration, are especially in need of a dedicated energy efficient solution. COUNTIS products with MID certification provide the guaranteed accuracy required for applications in which sub-billing of the electrical energy consumed is necessary. To meet this requirement, the **RETROFIT Line**

allows you to easily add metering points in electrical enclosures which are very restricted in terms of integration.

Advantages

High overall accuracy

A global system measuring accuracy of better than 1% in energy from 10 to 120% of nominal current.

Easy installation

TCO split-core transformers mean the power cables do not need to be disconnected. Operations are quicker and minimise the electrical disconnection time.

Proven products

The COUNTIS products are based on standard SOCOMEC ranges.

The RETROFIT Line consists of COUNTIS meters combined with TCO split-core current transformers. Together they allow measuring and metering single and three phase networks up to 600 A, even inside the most confined cabinet spaces.

Communication to Monitoring

The data from RETROFIT products can be transferred to a central monitoring system.

Guaranteed connections

The product is protected against phase/ neutral inversion and detects wiring errors. Commissioning has been simplified to ensure the device operates correctly: installation costs are therefore reduced.

The solution for



Strong points

- > High overall accuracy
- > Easy installation
- > Proven products
- Communication to a Monitoring system
- > Guaranteed connections

Conformity to standards

COUNTIS:

- > IEC 62053-21
- > IEC 62053-22
- > IEC 62053-23
- IEC 62053-31
- > EN 50470-3
- > EN 30470-3
- > EN 50470-1





66

Meters

Function

The **COUNTIS E4xR** is an active electrical energy meter designed for three-phase networks. It is used for connection via TCO up to 600 A. The **COUNTIS E42R** is a totalising meter allowing direct reading of the power consumed, using a pulse output. It is a dual tariff meter for dual tariff invoicing.

The $\mbox{COUNTIS E44R pack}$ offers MODBUS RTU communication via RS485 and includes 4 tariffs.

COUNTIS E42R and E44R are MID-certified (B + D module).

Technical characteristics⁽¹⁾

	(III)	(IIIac
	COUNTIS E42R	COUNTIS E44R
Current measurement		
Туре	TC/1 up to 600 A	TC/1 up to 600 A
Input consumption	0.2 VA per phase	0.2 VA per phase
Overload	24 A / 0.5 s	24 A / 0.5 s
Permanent overload	1.2 A	1.2 A
Minimum current measured	10 mA	10 mA
/oltage measurement		
Range of measurement	230 400 V ± 15 %	230 400 V ± 15 %
Input consumption	2 VA	2 VA
Permanent overload	280 V	280 V
Energy accuracy		
Active (according to EN 50470)	Class C	Class C
1) Features not mentioned are identical to those of COUNTIS E4x standard products.	· · · ·	

Front panel, terminals, case, connection

See the standard COUNTIS E range catalogue pages.

References					
Meters	Reference	Current transformers	Reference		
COUNTIS E42R	4850 3021	TCO 24 100/1	182T 4910		
COUNTIS E44R	4850 3022	TCO 24 250/1	182T 4925		
		TCO 36 400/1	182T 4940		
		TCO 36 600/1	182T 4960		

What are the advantages of a MID meter?

It allows to resell electricity

The MID directive guarantees safe and reliable metering. The meter is tamper-proof and its accuracy is guaranteed thanks to calibration on a metrology bench.

COUNTIS E42R and **E44R** are MID-certified (B + D module). It is mandatory and this means SOCOMEC is required to supply products which meet the design and manufacturing requirements imposed by this standard.

The specificity of MID product

- Standardised accuracy A, B or C: Socomec MID meters have a guaranteed accuracy class C \pm 0.5%.

- Tamper-proof devices: protection cover and seals are provided.

- Mandatory markings: CE + MID front and side marking confirms the compliance to modules B + D.
- Related Certificate: provided by Socomec, it formalizes the accuracy verification of the energy meter at four different current levels.



67


TCO - split-core current transformers

Function

The TCO small split-core current transformers must be only combined with COUNTIS RETROFIT energy meters.

The RETROFIT pack guarantees overall accuracy to within less than 1%.

Technical characteristics



	TCO 24	TCO 36
Internal diameter (mm)	24	36
Overall accuracy class ⁽¹⁾	1	1
Dimensions H x W x D (mm)	74.5 x 45 x 34	91 x 57 x 40.5

(1) Overall accuracy of the COUNTIS RETROFIT + TCO combination: (1) Global accuracy guaranteed when associating COUNTIS Retrofit + splitcore CT with load between 10 % to 120 % of In.

The advantages of TCO split-core current transformers

Wide current range

The TCOs accept a primary current between 100 and 600 A making it possible to connect at different points in the installation.

A guaranteed overall accuracy

Combined with the COUNTIS RETROFIT products, the TCO guarantees overall accuracy is better than 1%.

Compact

With their compact and open design, the TCOs are easily positioned on existing installations without the need to disconnect/reconnect the cables or modify the installation. Measurement points can therefore be placed in the most confined panels.



Services

Take advantage of the advice offered by an energy specialist

Socomec offers a full range of customised services for your energy efficiency requirements and can help you find the best solution:

- Implementation
- Training
- Electrical facility audit
- Project engineering.



For more details download our Service brochure available on our web site: www.socomec.com or contact your SOCOMEC office.





Think about it

COUNTIS Eci

Communicate consumption information whatever the energy (electricity, water, gas...) to a PC or PLC. Please see the COUNTIS Eci catalogue pages.



69